

MATERIAL SAFETY DATA SHEET TRIM SEALANT

GENERAL

Date	13/08/09
Revision Number	0
Date of First Issue	13/08/09
Manufacturer	Dodo Juice Ltd
Address	275 Desborough Ave, High Wycombe, Bucks HP11 2TL
Emergency	+44 (0)7990 518430, +44(0)1279 813222
Telephone Number	
Information	+44 (0)7990 518430
Telephone Number	

1. IDENTITY

Commercial Name	Dodo Juice
Product Description	Crystal resin sealant for coating and restoring plastic trim.
Identity (Label/List)	Supernatural Trim Sealant

2. COMPOSITION

	<u> </u>	
General	Proprietary blend.	

HAZARDOUS INGREDIENTS

Component	Petroleum distillates, aromatic hydrocarbon.
CAS No.	91203 5% PEL 10ppm, 64742-94-5
Symbol /	R11, R38, R65, R67.
Risk Phrase	509, S16, S23, S24, S33, S43 <i>A</i> , S60, S61, S62.
Classification/Symbol	Highly flammable/F
	Harmful/Xn

3. HAZARDS

Health	Irritating to skin.
	Harmful - may cause lung damage if swallowed.
	Vapours may cause drowsiness & dizziness.
Environmental	Moderately toxic.
Physical &	Extreme hazard. Vapour or liquid can readily form flammable
Chemical/Fire &	mixtures at temperature at or above the flash point.
Explosion	



4. FIRST AID MEASURES

Inhalation	Using approved respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.
Skin Contact	Wash with plenty of soap and water after use. Remove grossly contaminated clothing & launder/dry-clean before re-use.
Eye Contact	Hold eyelid open and rinse with plenty of water, until irritation subsides. If irritation persists, seek medical advice.
Ingestion	Do not induce vomiting. If victim vomits, turn into recovery position. Vomiting can cause chemical pneumonia. Get medical attention.

5. FIRE FIGHTING MEASURES

<u> </u>	O: T ZNC T ZOTT ZNO MC NOONCO	
Fire Fighting	Use water spray to cool exposed containers and to knock down	
Procedures	vapour. If possible, shut off the source of fuel to the fire.	
	Vapour is heavier than air and may travel a considerable	
	distance back to an ignition source and flashback.	
Fire Fighting Media	Use foam, dry chemical or carbon dioxide (CO2) to extinguish	
	fire. Water may be ineffective.	
Special Precautions	Containers may explode if exposed to fire. See section 4 'First	
	Aid Measures', and Section 10 'Stability & Reactivity'.	
Hazardous	Fumes, smoke, carbon dioxide (CO2), and carbon monoxide	
Combustion Products	(CO).	



6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	See Section 8.
Land Spills	Eliminate sources of ignition. Warn occupants in downwind areas of fire and explosion hazard. Prevent liquid from entering sewers, water courses or low areas. Keep public away. Shut off source, if possible to do so without hazard. Advise police if substance has entered a watercourse or sewer or has contaminated soil or vegetation. Take measures to minimize the effect on ground water. Contain spilled liquid with sand or earth. Use water spray to knock down vapour. Scrape up contaminated sand or earth with shovels or pails and place in suitable containers for disposal. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. See Section 4 'First Aid Measures', and Section 10 'Stability & Reactivity'.
Water Spills	Eliminate sources of ignition. Warn occupants and shipping in downwind areas of fire and explosion hazard and request them to stay clear. Notify port or relevant authority and keep public away. Shut off source, if possible to do so without hazard. Confine if possible. Remove from surface by skimming or with suitable absorbents. Spray with water mist to knock down vapour. If allowed by local authorities and environmental agencies sinking and/or suitable dispersants may be used in non-confined waters. Consult an expert on disposal of any recovered material and ensure conformity to local disposal regulations. See Section 4 "First Aid Measures", and Section 10 "Stability and Reactivity".

7. HANDLING AND STORAGE

7.11/11/10/22/10 /11/10	7.11/11/OCITIO /11/O O TOR/IOC	
Handling and	Keep container tightly closed. Avoid extremes of temperature	
Storage Precautions	and store in a cool, well ventilated place away from incompatible materials.	
	Do NOT handle or store near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do NOT pressurise, cut, heat or weld containers. Empty product containers may contain product residue. Container can remain hazardous when empty. Continue to observe all precautions.	



8. EXPOSURE CONTROL AND PERSONAL PROTECTION

U. LAI OBORE CON	TRUL AND PERSONAL PROTECTION
Engineering Control Measures/Ventilation	Use outdoors or in an adequately ventilated area. The use of local exhaust ventilation is recommended near the source. Use
Measures/ ventuation	
	explosion proof ventilation equipment.
Occupational	Napthalene PEL 10ppm
Exposure Limits	
Personal Protection	General advice - the use and choice of personal protection equipment is related to the hazard of the product, the workplace and the way the product is handled. In general, we recommend as a minimum safety precaution, safety glasses and clothes protecting arms legs and body be used. Respiratory protection - for the industrial user or handler, if using in air and exceeding concentration limits, it is recommended a half-face filter mask to protect against over exposure by inhalation. Use NIOSH approved respirator if spraying. Hand protection - when handling this product, it is recommended to wear chemical resistant gloves such as Viton, nitrile rubber or PVC. Eye protection - safety glasses with splash shields or face shield. Skin/body protection - protective apron, long sleeves,
	chemical resistant boots.
Environmental	See section 12.
Exposure Controls	

9. PHYSICAL AND CHEMICAL PROPERTIES

	GENERAL INFORMATION
Appearance	Colourless liquid
Odour	Aromatic
Freezing/Melting	<-60°C
Point	
Boiling Point / Range	182°C
	HEALTH, SAFETY & ENVIRONMENTAL INFORMATION
Flash Point	145°F TCC
Explosive Limits in	UEL - 7.5, LEL - 0.8
Air	



10. STABILITY AND REACTIVITY

Stability	Stable.
Conditions to Avoid	Heat, sparks, open flames and other sources of ignition.
Materials to Avoid	Strong oxidants / oxidising agents.
Hazardous	Carbon oxides formed when burned.
Decomposition	
Products	

11. TOXICOLOGICAL DATA

Tubalation	Vancuus consententians about accommonded consequed building		
Inhalation	Vapour concentrations above recommended exposure levels are		
	irritating to the eyes and the respiratory tract, may cause		
	headaches, drowsiness and dizziness, are anaesthetic and may		
	have other central nervous system effects.		
Skin Contact	Frequent or prolonged contact may cause irritation and		
	dermatitis.		
Eye Contact	Irritating. Can cause pain, reddening and watering of the eyes.		
Ingestion	Harmful or fatal if swallowed.		
	Dermal: LD50>2000		
	Oral: LD50>2000		
	Chronic Toxicity: No significant neurotoxic, blood, kidney or		
	other effects.		

12. ECOLOGICAL INFORMATION

Ecotoxicity	Moderately toxic.		
Environmental Mobility	Data not available.		
Environmental Degradability	Data not available.		



THEDODO@DODOJUICE.COM

13. DISPOSAL CONSIDERATIONS

Method	Use certified chemical waste disposal. This product is not		
	suitable for disposal by land fill or via municipal sewers, drains,		
	natural streams or rivers.		

14. TRANSPORT INFORMATION

Shipping Name	Combustible liquid, n.o.s.	
Hazard Class	Combustible	
Identification Number	UN 1993	
Packing Group	3	
Label Drum	None	
Placard Non-Bulk	Combustible (>1000lbs)	
Placard Bulk	UN 1993	
Shipping Description	Combustible liquid, n.o.s. (Petroleum Hydrocarbon) UN1993,	
	PG 3	

15. REGULATORY INFORMATION

Classification and labelling according to EEC Directives.

This classification results from test data and/or assessment.

THIS CIUSSITICUTION I	esulis i	rom lest data and/or assessment.		
Classification/Symbol	HIGHLY FLAMMABLE/F			
	HARMFUL/Xn			
Governing Directive:	DANGEROUS SUBSTANCES DIRECTIVE 67/548/EC, AS			
	MODIFIED			
Label Name:	TBA			
Nature of Special	R11	highly flammable.		
Risk:	R38	irritating to skin		
	R65	harmful: may cause lung damage if swallowed		
	R67	vapours may cause drowsiness and dizziness		
Safety Advice:	509	keep container in a well ventilated place		
	516	keep away from sources of ignition - no smoking		
	523	do not breathe gas/fumes/vapour/spray		
	524	avoid contact with skin		
	533	take precautionary measures against static charges		
	543 <i>A</i>	in case of fire use foam, dry powder or carbon		
	dioxide (CO2)			
	560	this material and/or its container must be disposed		
	of as hazardous waste			
	561	avoid release to the environment. Refer to special		
	instructions/safety data sheet.			
	562	if swallowed, do not induce vomiting: seek medical		
	advice immediately and show this container or label			



16. OTHER INFORMATION

Cured residue may be difficult to remove from fabrics, including application cloths.

DISCLAIMER: The data herein is given in good faith and based on the best of our knowledge at the date of issue of this document. Each user is responsible for determining the suitability of the material in their particular application and that such usage complies with applicable legislative rules and regulations. However, no representation, warranty of guarantee is made as to its accuracy, reliability or completeness.